




F **FLOATING**
design floating floor



NATURAL SHIELD® water base urethane varnish
Natural cork decor
High-density fiberboard
Cork granulate underlayment

Comfortable living is not a luxury.

- OK RADIANT HEATING
- PHthalate FREE
- EASY TO REPAIR
- ANTI-ALLERGY
- RESISTANT
- ECO-FRIENDLY
- ANTI-SLIPPERY
- RECYCLABLE

TEST	STANDARD
Dimensions / Thickness	EN 427 / EN 428
Weight	EN 430
Level of use Domestic	
Level of use Commercial	
Dimensional Stability	EN 434
Squareness	EN 427
Straightness	EN 427
Resistance against staining	EN 438
Resistance to scratching	EN 438-2
Residual Indentation	EN ISO 24343-1
Fire Resistance	DIN EN 13501
Anti-sliding properties	EN13893
Formaldehyde emission	EN 717-1
Thermal Resistance	EN 12667
Impact Sound Reduction	EN 140
Impact Insulation Class IIC	ASTM E 492-09 / ASTM E 989-89
Locking strenght - short side joints - long side joints	ISO 24334

EXCLUSIVE	ETHERNAL
900 x 300 x 11 mm	900 x 300 x 10 mm
8 Kg/m ²	
23	
31	
0,1%	
< 0,3 mm	
< 0,2 mm	
Grade 1- 5	
4 N / Grade 3	
0,13 mm	
Cfl-s1	
DS	
E1	
0,1 (m2K)/W	
19 dB	17dB
55 dB	
4.8 kN/m	
4.2 kN/m	



Os Fundos Europeus mais próximos de si.